

TRACK 48V

B02V-X33J5V-00



Alimentador TRACK 48V

indeluZ

B32 / B34 / B35: 4-wire rail, with two options for use: option 2 circuits (2x +/-15A/0-60V dc) or option 1 circuit (+/-15A/0-60V)+ Data Bus (D+/D-). The DC voltage connection is 48V. The rail can support 25kg with a distance between fixings of 0.9m. B33: Double rail 8 conductors, 4 on top and 4 on bottom. On each side, with two options for use: option 2 circuits (2x +/-15A/0-60V dc) or option 1 circuit (+/-15A/0-60V)+ Data Bus (D+/D-). The DC voltage connection is 48V. The rail can support 25kg with a distance between fixings of 0.9m.

DATOS GENERALES

Categoría	Accesorios
Familia	Track 48V
Ubicación	Interior
Instalación	Techo
Material del cuerpo	Aluminio
ETIM class	EC002556
EAN	8433264105648

FUENTES DE LUZ

HACES DE LUZ

DATOS TÉCNICOS

Dimensiones	Altura x Anchura x Longitud (mm): 30 x 40 x 300
IP	IP20
Clase eléctrica	Clase II
Frecuencia	50/60 Hz
Voltaje de entrada	220-240V AC V
Potencia total	120 W
Potencia	120,0 W

NOTAS

Superficie

Led Driver 220-240V AC remote / 48V DC